



Gary Nelson

The Energy Conservatory

Minneapolis, MN

DG-700 Replaces the DG-3

- Since July 2003, DG-3 discontinued.
- DG-700 is the standard Blower Door and Duct Blaster® instrument.
- DG-700 is designed to operate with all TEC testing equipment.

Introduction

Blower Door

Duct Blaster

Combustion Safety

Demonstrations

New Developments

DG-700 Sim

TECTITE

TECLOG

DG-700



DG-3





The ENERGY
CONSERVATORY

DG-700's Added Features

- 2 pressure sensors with simultaneous display of both building (or duct) pressure and fan flow.
- No need to switch between channels - more intuitive for airtightness testing.
- Display always shows which air flow device (fan) and configuration (flow ring) are chosen.

[Introduction](#)

[Blower Door](#)

[Duct Blaster](#)

[Combustion Safety](#)

[Demonstrations](#)


[New Developments](#)

[DG-700 Sim](#)

[TECTITE](#)

[TECLOG](#)

*Building
or Duct
Pressure
(Pa)*



*Fan Flow
(CFM)*



The ENERGY
CONSERVATORY

DG-700 Blower Door Features

- Specialized **PR/ FLOW @50** Mode for One-Point Blower Door tests.
 - ❑ Gauge displays CFM50 on Channel B. (Can't Reach 50 Factor is built-in to the flow reading)
 - ❑ Saves time - no need to adjust test pressure to exactly 50 Pa - just get close (45 - 55).
 - ❑ Very stable readings
 - ❑ In very leaky buildings, displays leakage estimate if building pressure is at least 10 Pa.



[Introduction](#)

[Blower Door](#)

[Duct Blaster](#)

[Combustion Safety](#)

[Demonstrations](#)

[New Developments](#)

[DG-700 Sim](#)

[TECTITE](#)

[TECLOG](#)



The ENERGY
CONSERVATORY

DG-700 Blower Door Features

➤ Why conduct One-Point Blower Door tests using **PR/ FLOW @50?**

- ❑ *Fast and easy.*
- ❑ *No software required.*
- ❑ *Reasonable airtightness results.*

[Introduction](#)

[Blower Door](#)

[Duct Blaster](#)

[Combustion Safety](#)

[Demonstrations](#)

[New Developments](#)

[DG-700 Sim](#)

[TECTITE](#)

[TECLOG](#)






The ENERGY
CONSERVATORY

DG-700 Blower Door Features

- Computer interface for automated Blower Door testing (Multi-Point test).
 - ❑ *Laptop computer.*
 - ❑ *TECTITE software (3.0 +).*
 - ❑ *Modified fan speed controller with comm. jack.*
 - ❑ *Cabling (serial cable and fan control cable).*



**Serial
Communication
Port**

**Fan Control
Jack**

Introduction

Blower Door

Duct Blaster

Combustion Safety

Demonstrations

New Developments

DG-700 Sim

TECTITE

TECLOG

DG-700 Blower Door Features

- Why conduct Multi-Point automated Blower Door tests?
 - ❑ *Reduces operator errors, improves consistency between tests.*
 - ❑ *Improved accuracy in windy weather, and provides overall estimate of test accuracy.*
 - ❑ *Better method for estimating leakage areas.*



Introduction

Blower Door

Duct Blaster

Combustion Safety

Demonstrations

New Developments

DG-700 Sim

TECTITE

TECLOG



The ENERGY
CONSERVATORY

DG-700 Blower Door Features

➤ BASELINE Feature:

- ❑ *Baseline feature makes it simple to always take a baseline pressure measurement during the Blower Door test. (Baseline is the building pressure before turning on the Blower Door fan and fan sealed).*
- ❑ *Baseline reading is stored in the gauge.*
- ❑ *Gauge displays the baseline adjusted house pressure (i.e. baseline reading is automatically subtracted from the building pressure).*
- ❑ *Eliminates need to calculate adjusted target pressure.*

[Introduction](#)

[Blower Door](#)

[Duct Blaster](#)

[Combustion Safety](#)

[Demonstrations](#)

[New Developments](#)

[DG-700 Sim](#)

[TECTITE](#)


[TECLOG](#)



The ENERGY
CONSERVATORY

DG-700 Duct Testing Features

- Specialized **PR/ FLOW @25** Mode for Total Duct Leakage tests.
 - ❑ Gauge displays CFM25 on Channel B. (Can't Reach 25 Factor is built-in to the flow reading)
 - ❑ Saves time - no need to adjust test pressure to exactly 25 Pa - just get close (20 - 30).
 - ❑ Very stable readings
 - ❑ In very leaky duct systems, displays leakage estimate if Duct Pressure is at least 5 Pa.



[Introduction](#)

[Blower Door](#)

[Duct Blaster](#)

[Combustion Safety](#)

[Demonstrations](#)

[New Developments](#)

[DG-700 Sim](#)

[TECTITE](#)

[TECLOG](#)




The ENERGY
CONSERVATORY

DG-700 Duct Testing Features

- For Leakage to Outside tests (simultaneous use of Duct Blaster and Blower Door), use general purpose **PR/ FLOW** Mode.

- ❑ *With Blower Door pressurizing building to 25 Pa, Duct Blaster adjusted to create zero pressure between ducts and building.*
- ❑ *Only advantage of DG-700 with this test is simultaneous display of duct pressure and fan flow, and device and configuration indicators.*



[Introduction](#)

[Blower Door](#)

[Duct Blaster](#)

[Combustion Safety](#)

[Demonstrations](#)

[New Developments](#)

[DG-700 Sim](#)

[TECTITE](#)

[TECLOG](#)




The ENERGY
CONSERVATORY


Combustion Safety Testing Features

- Use the Baseline feature to measure worst-case fan depressurization.


- ☐ *When exhaust fans are turned on, gauge will display change in pressure caused by fans.*



(Fan Off) - Measuring Baseline Pressure



(Fan Off) - Baseline Adjusted Pressure



(Fan On) - Change in Pressure

[Introduction](#)

[Blower Door](#)

[Duct Blaster](#)

[Combustion Safety](#)

[Demonstrations](#)

[New Developments](#)

[DG-700 Sim](#)

[TECTITE](#)


[TECLOG](#)



The ENERGY
CONSERVATORY

Combustion Safety Testing Features

- Connect DG-700 to laptop and simultaneously record fan depressurization and vent performance.
- TECLOG software is available at no-charge.



Introduction

Blower Door

Duct Blaster

Combustion Safety

Demonstrations

New Developments

DG-700 Sim

TECTITE

TECLOG



The ENERGY
CONSERVATORY

DG-700 Demonstrations

[Introduction](#)

[Blower Door](#)

[Duct Blaster](#)

[Combustion Safety](#)

[Demonstrations](#)

[New Developments](#)

[DG-700 Sim](#)

[TECTITE](#)

[TECLOG](#)



The ENERGY
CONSERVATORY

New Developments

- TECTITE Mechanical Ventilation Guideline.
 - ❑ *The latest version of TECTITE incorporates a mechanical ventilation guideline based on ASHRAE Standard 62.2.*
 - ❑ *Estimates the required mechanical ventilation rate for the building based on occupancy and Blower Door test results.*

Mechanical Ventilation Guideline
Recommended Whole Building Mechanical
Ventilation Rate: 28.1 CFM

[Introduction](#)

[Blower Door](#)

[Duct Blaster](#)

[Combustion Safety](#)

[Demonstrations](#)

[New Developments](#)

[DG-700 Sim](#)

[TECTITE](#)


[TECLOG](#)



The ENERGY
CONSERVATORY

New Developments

- Infrared Thermography with a Blower Door.
 - ❑ *View building components before Blower Door fan is turned on (detect missing or poorly installed insulation).*
 - ❑ *View components with Blower Door fan running (differences indicate air leakage paths).*



Introduction

Blower Door

Duct Blaster

Combustion Safety

Demonstrations

New Developments

DG-700 Sim

TECTITE

TECLOG



The ENERGY
CONSERVATORY

New Developments

- Zone Pressure Testing Software.
 - ❑ Software estimates air leakage of attached building zones (e.g. garage, attic).
 - ❑ Manually input Blower Door test data and zone pressure measurements into software.
 - ❑ Zone leakage test results include estimate of test uncertainties.
 - ❑ Available for free from TEC website.

ZPD Step 6 - Zone Leakage Results

Test ID: 1243 Elm

Zone Tested = attic

* Zone Shifted by -17.8 Pa, From -17.4 to -35.2

	Leakage Range	
	min	max
house to attic leakage (sq. in.)	81	177
attic to outside leakage (sq. in.)	137	251
leakage through zone (CFM50)	610	1254

< Previous * Adjusted to a house pressure of 50 Next >

[Introduction](#)

[Blower Door](#)

[Duct Blaster](#)

[Combustion Safety](#)

[Demonstrations](#)

[New Developments](#)

[DG-700 Sim](#)

[TECTITE](#)

[TECLOG](#)



The ENERGY
CONSERVATORY

New Developments

- Alternative Duct Testing Procedures.
 - ❑ *Delta-Q (attempts to measure actual leakage using a series of 4 Blower Door tests). Requires automated tests and software.*
 - ❑ *Blower Door Subtraction (airtightness estimated by comparing automated Blower Door test results with registers sealed and unsealed). Requires automated tests and software.*
 - ❑ *TEC is working on proto-type software for both methods.*



[Introduction](#)

[Blower Door](#)

[Duct Blaster](#)

[Combustion Safety](#)

[Demonstrations](#)

[New Developments](#)

[DG-700 Sim](#)

[TECTITE](#)

[TECLOG](#)



The ENERGY
CONSERVATORY

TEC Website

- www.energyconservatory.com
- Available to download:
 - ❑ *Product Manuals*
 - ❑ *TECLOG Software.*
 - ❑ *Zone Pressure Diagnostics Software.*
 - ❑ *30-day Demo of TECTITE & TECBLAST Software.*
 - ❑ *Check What's New.*

[Introduction](#)

[Blower Door](#)

[Duct Blaster](#)

[Combustion Safety](#)

[Demonstrations](#)

[New Developments](#)

[DG-700 Sim](#)

[TECTITE](#)

[TECLOG](#)